

GARDENING AND FORESTRY



ORLEN OIL TRAWOL 30

OUALITY CLASS: API: SG/CD

VISCOSITY GRADE: SAE 30 - one season, summer oil

GENERAL FEATURES:

High quality, one season, mineral oil intended for four-stroke farming machine engines. The oil quality is guaranteed by especially selected manufacturing process based on highly refined mineral oil bases and high quality enriching additives.

- ORLEN OIL Trawol 30 provides perfect properties:
 permanent lubricating film in high thermal and mechanical loads,
 - efficiency due to low vapour looses,
 - very good resistance to oxidation which protects formation of "black sludge",
 - corrosion protection,
 - prevented formation of high temperature deposits,
 - fully mixable with other oils of the same viscosity grade and quality class.

APPLICATION:

ORLEN OIL Trawol 30 is a high quality engine oil recommended for:

- mowers
- soil millers.
- ploughs,
- other garden equipment with four-stroke petrol engines with or without a catalyst.

PHYSICAL AND CHEMICAL PROPERTIES:

Parameters	Units	Typical values
SAE viscosity grade	-	30
kinematic viscosity at 100°C	mm²/s	9.5
viscosity index	-	112
flow temperature	⁰ C	-28
ignition temperature	0C	230
base value TBN	mg KOH/g	8.6
sulphate ash	%	0.6
water content	% (v/v)	no content
corrosiveness at 100°C for 3 hours to copper	corrosion grade	1

ORLEN OIL Sp. z o.o. ul. Elblaska 135, 80-718 Gdańsk, tel. +48 12 665 55 00, fax +48 12 665 55 01, e-mail: <u>centrala@orlenoil.pl</u>, **infolinia: 0 801 102 103**





GARDENING AND FORESTRY

Note: The above values of physical and chemical properties are typical values. Actual values are specified in quality certificates enclosed with each product lot.

VERSION:

1 / 2023.07.17

